



Perfect to heat up bigger public rooms, bigger rooms like at the office or in the basement like recreation rooms.

The double convector heater is 60 % more heat efficient, because of it's construction and air flow. (See explanation, press here!). The deep of the convector is 45 mm.

Technical information

Thermostat features:

Thermostat sensitivity: +0,1°C to 0,4°C.

Thermostat control: From +7°C to +35°C.

Anti-freeze function: From +7°C.

The electronically pulse thermostat pulses each 45 second.

Its air controlled and reacts on the temperature of the room.

Approvals:

S CE CB EN IP31

The convector series has **5 years guarantee**

Cables and wall holders:

230V and 400V comes with wall holders and 3 conductor cable.

Heating requirements:

The heating requirement can be calculated to app. 70W/m² or 30W/m³.

Measure from wall:

800 watt to 2000 watt builds 131 mm from the wall incl. Wall holders.

No.	Art no. L X W mm	Description	Type of thermostat	Watt	Volt	Weight Kg
1	900/600/DK2EE	Electric oil filled double convector radiator	Electronically	2000	230	35
2	1400/300/DK2EE	Electric oil filled double convector radiator	Electronically	1600	230	28
3	700/300/DK2EE	Electric oil filled double convector radiator	Electronically	800	230	18
4	900/600/DK3EE	Electric oil filled double convector radiator	Electronically	2000	400	35
5	1400/300/DK3EE	Electric oil filled double convector radiator	Electronically	1600	400	28
6	700/300/DK3EE	Electric oil filled double convector radiator	Electronically	800	400	18