



A nice designed radiator for portable and permanent use

**A nicely designed energy saving, easy handled radiator for permanent use.**

**Technical information**

Thermostat features:

Thermostat sensitivity: +0,4°C.

Thermostat control: From +5°C to +35°C.

Anti-freeze function: From +5°C.

400V radiators are suited for central/external control through a pilot cable.

**Cables and wall holders:**

230V comes with feet and wall holders. 1,4 m long earthed cable with plug.

400V comes with wall holders for permanent installation and a 1,4m long cable without plug.

**Over voltage/overheat protection:**

The thermostat is provided with an over voltage protection and overheat protection.

**Approvals:**

S CE CB EN IP34

**3 years guarantee**

**Heating requirements:**

The heating requirement can be calculated to app. 70W/m<sup>2</sup> or 30W/m<sup>3</sup>.

No.	Art no. L X W mm	Description	Type of thermostats	Watt	Volt	Weight Kg
1	900/600/E2P	Electric oil filled radiator	Electronically	1000	230	10
2	1400/300/E2P	Electric oil filled radiator	Electronically	800	230	9
3	700/600/E2P	Electric oil filled radiator	Electronically	750	230	8
4	700/300/E2P	Electric oil filled radiator	Electronically	400	230	5
5	900/600/E3E	Electric oil filled radiator	Electronically	1000	400	10
6	1400/300/E3E	Electric oil filled radiator	Electronically	800	400	9
7	700/600/E3E	Electric oil filled radiator	Electronically	750	400	8
8	700/300/E3E	Electric oil filled radiator	Electronically	400	400	5

[>Radiators](#) [>Print page](#) [>www.wosab.se](http://www.wosab.se)